



Material	Aluminum		
lightsource	2x COB LED		
Led type	Bridgelux Vesta of Bridgelux V SERIES		
Color temperature	Dim to Warm, 2700K,3000K,4000K		
CRI	>90		
placement	Ceiling with recessed adapter		
Diameter mount	120mm		
Light direction	Down/adjustable		
Optics	2x lens		
Indoor/outdoor	Indoor		
Beam angle	Measured: 20° tot 84° Verstelbaar met Zzoom ring		
Beam angle Adjustability	Measured: 20° tot 84° Verstelbaar met Zzoom ring 360 graden		
	3		
Adjustability	360 graden		
Adjustability Driver	360 graden Included, 500mA phase cut dimmable		
Adjustability Driver Ingangsspanning	360 graden Included, 500mA phase cut dimmable 230V		
Adjustability Driver Ingangsspanning Power consumed	360 graden Included, 500mA phase cut dimmable 230V 21W		
Adjustability Driver Ingangsspanning Power consumed Colors	360 graden Included, 500mA phase cut dimmable 230V 21W Black, Brass, Gold		

1



Values below are	per light source
------------------	------------------

•	3		
2700K Ra 90			
Driver output (mA)	250	350	500
Forward voltage	30,4	31	31,9
Lumen output	1008	1380	1911
Efficiency lm/W	147	142	134
Watt (led)	7,6	10,9	16
3000K Ra 90			
Driver output (mA)	250	350	500
Forward voltage	30,4	31	31.9
Lumen output	1058	1448	2005
Efficiency lm/W	154	149	141
Watt (led)	7,6	10,9	16
4000K Ra 90			
Driver output (mA)	250	350	500
Forward voltage	30,4	31	31.9
Lumen output	1069	1464	2026
Efficiency lm/W	150	150	142
Watt (led)	7,6	10,9	16
watt (tod)	,,0	10,,	10
Dim to warm			
Driver output (mA)	250	350	
Forward voltage	31,7	33,8	
Lumen output	900	1313	
Efficiency lm/W	113	111	
Watt (led)	8,3	11,8	

Description	Item code
big Balls black 2700K (dimmable driver included)	A-1000-20B-L2X
big Balls black 3000K (dimmable driver included)	A-1000-20B-L3X
big Balls black 4000K (dimmable driver included)	A-1000-20B-L4X
Big Balls black dim to warm (dimmable driver included)	A-1000-20B-L5X