


## Orb suspended





Material	Aluminum/glass				
lightsource	2x COB LED				
Led type	Bridgelux Vesta of Bridgelux V SERIES				
Color temperature	Dim to Warm, 2700K,3000K,4000K				
CRI	>90				
placement	Ceiling diameter ceiling mount Ø126mm				
Standard suspension cable	2mtr (longer cables on request available)				
length					
Light direction	Up / down				
Optics	2x lens				
Indoor/outdoor	Indoor				
Beam angle	measured: 60° (up and down)				
Adjustability	360 graden				
Driver	Integrated in mount, phase cut dimmable 500mA (other driver types have to be installed externally)				
voltage	230V				
Power consumed	21W				
Colors	Black, Brass, Gold				
Dimensions	Ø122 x 182mm				
IP class	IP20				
Beam	Soft beam through diffusers, taking out the diffusors will give a sharp beam.				

1



## Orb suspended

				_		
Values	held	7\//	are	tor	each	l ed
Valacs	DCC	J V V	ui c	101	Cucii	LCU

2700K Ra 90	
Driver output (mA)	250
Forward voltage	30,4
Lumen output Led	1008
Efficiency lm/W	147
Watt (led)	7,6
3000K Ra 90	
Driver output (mA)	250
Forward voltage	30,4
Lumen output Led	1058
Efficiency lm/W	154
Watt (led)	7,6
4000K Ra 90	
Driver output (mA)	250
Forward voltage	30,4
Lumen output Led	1069
Efficiency lm/W	150
\A/ ++ (1 - 1)	
Watt (led)	7,6
watt (led)	
Watt (led)  Dim to warm	
Dim to warm	
	7,6
Dim to warm Driver output (mA)	7,6 250
Dim to warm Driver output (mA) Forward voltage	7,6 250 31,7



## Orb suspended

Description	Item code
Orb suspended black 2700k (dimmable driver included)	A-1101-10B-L2X
Orb suspended black 3000k (dimmable driver included)	A-1101-10B-L3X
Orb suspended black 4000k (dimmable driver included)	A-1101-10B-L4X
Orb suspended black dim to warm (dimmable driver included)	A-1101-10B-L5X
Orb suspended gold 2700K (dimmable driver included)	A-1101-10E-L2X
Orb suspended gold 3000K (dimmable driver included)	A-1101-10E-L3X
Orb suspended gold 4000K (dimmable driver included)	A-1101-10E-L4X
Orb suspended gold dim to warm (dimmable driver included)	A-1101-10E-L5X
Orb suspended Brass-plated 2700K (dimmable driver included)	A-1101-10D-L2X
Orb suspended Brass-plated 3000K (dimmable driver included)	A-1101-10D-L3X
Orb suspended Brass-plated 4000K (dimmable driver included)	A-1101-10D-L4X
Orb suspended Brass-plated dim to warm (dimmable driver included)	A-1101-10D-L5X